

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (original): An optical apparatus comprising:  
a container filled with a gas containing hydrogen;  
an optical element of silica glass, accommodated in said container; and  
a light source emitting coherent light,  
wherein the hydrogen has a partial pressure of 0.01 to 500 kgf/cm<sup>2</sup>, and  
wherein said optical element and said light source are aligned so that the coherent light emitted from said light source is incident upon said optical element.
2. (original): An optical apparatus according to claim 1, wherein said optical element is subjected to a heat treatment in a hydrogen atmosphere before being accommodated in said container.
3. (original): An optical apparatus according to claim 2, wherein the pressure in the hydrogen atmosphere during heat treatment is set in a range from 1 to 500 kgf/cm<sup>2</sup>, and the temperature in the hydrogen atmosphere is set in a range from 80 to 500°C.

4. (original): An optical apparatus according to claim 1, wherein the hydrogen concentration of the gas containing hydrogen is set to be less than 4% by volume.

5. (original): An optical apparatus according to claim 1, wherein said container further comprises a valve, said valve being of a construction for connection to an external element to supply at least hydrogen from the external element into said container.

6. (original): An optical apparatus according to claim 5, wherein said valve is selected from the group consisting of a check valve and a shut-off valve.

7. (original): An optical apparatus according to claim 1, wherein said container further comprises at least an inlet and at least an outlet, wherein the gas containing hydrogen flows through said container from said at least an inlet to said at least an outlet.

8. (original): An optical apparatus according to claim 1, wherein the gas containing hydrogen is pure hydrogen.

9. (original): An optical apparatus according to claim 1, wherein the optical element includes at least one of a lens, an optical fiber, a mirror, a prism, an optical filter, and a reticle.

10. (original): An optical apparatus according to claim 1, wherein said light source is an excimer laser, emitting ultraviolet light.

11. (original): An optical apparatus comprising:  
a container filled with a gas containing hydrogen, said container having a first light transmission window; and  
an optical element accommodated in said container;  
wherein the hydrogen has a partial pressure of 0.01 to 500 kgf/cm<sup>2</sup>, and  
wherein said optical element is aligned to receive light incident upon said first light transmission window.

12. (original): An optical apparatus according to claim 11, wherein said optical element is subjected to a heat treatment in a hydrogen atmosphere before being accommodated in said container.

13. (original): An optical apparatus according to claim 12, wherein the pressure in the hydrogen atmosphere during heat treatment is set in a range from 1 to 500 kgf/cm<sup>2</sup>, and the temperature in the hydrogen atmosphere is set in a range from 80 to 500°C.

14. (original): An optical apparatus according to claim 11, wherein the hydrogen concentration of the gas containing hydrogen is set to be less than 4% by volume.

15. (original): An optical apparatus according to claim 11, wherein said container further comprises a valve, said valve being of a construction for connection to an external element to supply at least hydrogen from the external element into said container.

16. (original): An optical apparatus according to claim 15, wherein said valve is selected from the group consisting of a check valve and a shut-off valve.

17. (original): An optical apparatus according to claim 11, wherein said container further comprises at least an inlet and at least an outlet, wherein the gas containing hydrogen flows through said container from said at least an inlet to said at least an outlet.

18. (original): An optical apparatus according to claim 11, wherein the gas containing hydrogen is pure hydrogen.

19. (original): An optical apparatus according to claim 11, wherein said light transmission window is a lens.

20. (original): An optical apparatus according to claim 11, wherein the optical element includes at least one of a lens, an optical fiber, a mirror, a prism, an optical filter, and a reticle.

21. (original): An optical apparatus according to claim 11, said container further comprising a second light transmission window, arranged to transmit the light incident upon said first transmission window after said light is reflected by, or transmitted through, said optical element.

22. (withdrawn): A method of irradiating an optical element with ultraviolet light while protecting the optical element from radiation-induced defects, comprising steps of:

heat treating the optical element comprising silica glass in a hydrogen atmosphere;

accommodating the optical element in a container after heat treatment;

filling the container with a gas containing hydrogen after accommodating the optical element;

setting the partial pressure of the hydrogen in the filled container to be in a range of 0.01 to 500 kgf/cm<sup>2</sup>; and

irradiating the optical element in the filled container with ultraviolet light.

23. (withdrawn): A method according to claim 22, wherein said step of heat treating includes contemporary steps of:

setting a pressure of the hydrogen atmosphere to be 1 to 500 kgf/cm<sup>2</sup>;

setting a temperature of the hydrogen atmosphere to be 80 to 500 °C.

24. (withdrawn): A method according to claim 22, further comprising a step of:  
flowing the gas containing hydrogen through the container, after the step of filling  
the container, while maintaining the hydrogen at the partial pressure of 0.01 to 500 kgf/cm<sup>2</sup>.

25. (withdrawn): A method according to claim 22, further comprising a step of:  
sealing the container after the step of filling the container.

26. (withdrawn): A method according to claim 22, further comprising a step of:  
setting the concentration of the hydrogen filling the container to be less than 4%  
by volume.

27. (New): An optical apparatus according to claim 1, wherein the partial pressure of  
hydrogen is set in a range from 300 to 500 kgf/cm<sup>2</sup>.

28. (New): An optical apparatus according to claim 11, wherein the partial pressure  
of hydrogen is set in a range from 300 to 500 kgf/cm<sup>2</sup>.